


**TRAC-MASTER®**

Avant Garde

**T381L, T382L, T383L,  
T385L & T387L**
**DIMMER COMPATIBILITY**

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

**DIMMER COMPATIBILITY**
**Incandescent and Magnetic Low Voltage - Forward Phase Dimming**

• Dimmable with the use of most forward phase dimmers • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 50% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model.

Example: Fixture Rating = 10W  
 Dimmer Rating = 600W  
 Equivalent Incandescent Load (ELL) Factor = 50% (0.5)  
 $(600/10) \times 0.5 = 30$  Fixtures per Dimmer

**Juno Qualified Dimmers include:**
**Lutron® Model Numbers:**

- Glyder® GLV-600
- Diva® DV-600P
- Skylark® SLV-600P

**Leviton® Model Numbers:**

- Sureslide 6633
- Sureslide 6613-PLW

**Electronic Low Voltage - Reverse Phase Dimming**

• Dimmable with the use of most electronic low voltage dimmers • Electronic low voltage dimmers require a neutral wire in the wall box • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 75% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model.

Example: Fixture Rating = 10W  
 Dimmer Rating = 600W  
 Equivalent Incandescent Load (ELL) Factor = 75% (0.75)  
 $(600/10) \times 0.75 = 45$  Fixtures per Dimmer

**Juno Qualified Dimmers include:**
**Lutron® Model Numbers:**

- Diva® DVELV-600P
- Maestro® MAELV-600
- RadioRA2 RRD-6NA
- Homeworks LP-RPM-4A
- Grafik Eye PA Power Module PHPM-PA-120

**Leviton® Model Numbers:**

- Vizia VPE06-1LX

Consult technical services for additional information regarding other dimmer model qualification.