

PRODUCT DESCRIPTION

Recessed adjustable PAR20/PAR16 luminaire with 31/4" aperture and precision geared hot-aiming. Fixture has 50° visual cutoff to lamp and lamp image. Sealed Air-Loc housing eliminates leak-paths to ensure maximum energy savings and controls plenum sound transmission. IC rated housing for use in direct contact with insula-

PRODUCT SPECIFICATIONS

Trims Style Trim Ring, Self Flanged and Flush Mount Trims utilize torsion spring retention for tight, secure fit to ceiling • Trim ring features beveled knife edge for clean ceiling interface • Self Flanged reflectors with polished or optional white painted flange • Flush Mount trims must be used with FMA4 Flush Mount Adapter.

Socket Medium base porcelain socket with nickel plated copper

Lamp One 50W PAR20 or 60W PAR16 lamp max. (See trim for max. lamp rating)

Adjustability Acu-Aim[™] precision geared hot-aiming achieves 370° rotation, 40° tilt • Optimized center lamp beam optics translates lamp forward as it is aimed off nadir, insuring maximum light and low brightness • Black aiming mechanism with shield prevents visibility into fixture and preserves dark aperture • Shield hinges out of way to facilitate maintenance.

Codes/Labels UL and cUL listed for direct contact with insulation, through-branch wiring, damp locations (wet location with approved trims) • Meets energy code Air Leakage requirements per ASTM E283 • Product thermally protected • Union made.

Proprietary Bar Hanger System Patent pending Pro-VITM, telescoping bar hanger system with locking set screws, permits quick placement of housing within 24" O.C. joists or suspended ceilings

- Robust bar eliminates flexing regardless of fixture position
- Integral T-bar notch with locking tabs secures housing to suspended ceiling grid • Captive bugle-headed ring shank nail for quick onestep installation • Bar Hanger foot aligns to bottom of construction joist and breaks away for use in suspended ceilings.

Junction Box Rated for 4 No. 12 AWG 90° C through branch circuit conductors and includes (6) ½", (1) ¾", and (4) Non-metallic sheathed cable knock-outs • Push-in electrical connectors for field

Housing/Mounting Frame Steel plaster frame and aluminum housing painted black for visually dark interior • V-Notch in plaster frame aids fixture alignment during installation • Patent pending Tru-Line™ Adjustment Mechanism featuring +/- ½" translation aids fixture alignment after installation, prior to drywall.

Ceiling Thickness 1/2" – 7/8" ceiling standard • For thicker ceilings, order CTA4N-125 (7/8"-1 1/4"), CTA4N-163 (1 1/4"-1 5/8) or CTA4N-200 (1 5/8" - 2").

RECESSED ADJUSTABLE

3-1/4" APERTURE


IC Rated, PAR 16 or PAR 20 Halogen

IC13N

Project:	
Fixture Type:	
Location:	
Contact/Phone:	



DIMENSIONS



4 1/4" CEILING CUTOUT (4 3/8" FOR FLUSH MOUNT)

Housings	
Catalog #	Description
IC13N	Line Voltage Adjustable Recessed

Accessories

Cat. # **Description** CTA4N-125

1 1/4" Thick Ceiling Adapter 1 5/8" Thick Ceiling Adapter CTA4N-163 2" Thick Ceiling Adapter CTA4N-200 FMA4 Flush Mount Adapter

To order, specify catalog number.



Lamp Ratina

60W PAR 16/ 50W PAR20



3 1/4" RECESSED ADJUSTABLE IC13N, PAR16 or PAR20 Halogen

Trim Selection (Trim Ring, Self Flanged, Flush Mount)

437NWHZ-WH†* Wheat Haze Alzak® Cone

Description

DOWNLIGHT (Trim Ring Catalog # Shown)

Deep Downlig

Cat. No.



ght Cone		
437NB-ABZ	Black Alzak® Cone	60W PAR 16/
437NB-SC	Black Alzak® Cone	50W PAR20
437NB-WH†*	Black Alzak® Cone	
437NC-WH†*	Clear Alzak® Cone	
437NG-WH [†] *	Gold Alzak® Cone	
437NHZ-SC	Haze Alzak® Cone	
437NHZ-WH [†] *	Haze Alzak® Cone	
437NWHZ-ABZ	Wheat Haze Alzak® Cone	

Deep Downlight Baffle



434NB-ABZ	Black Baffle	60W PAR 16/
434NB-SC	Black Baffle	50W PAR20
434NB-WH	Black Baffle	
434NW-WH	White Baffle	

Downlight 1



1/4" Pinhole		
4337N-ABZ	Black Alzak® Reflector	60W PAR 16/
4337N-SC	Black Alzak® Reflector	50W PAR20
4337N-WH**	Black Alzak® Reflector	

Downlight Regressed 1 3/4" Pinhole



4307N-WH** Black Alzak® Reflector 60W PAR 16/ 50W PAR20

LENSED (Trim Ring Catalog # Shown)

Downlight Lensed Trim





432NB-WH [†] *	Black Alzak® Cone	45W PAR 16/
432NC-WH†*	Clear Alzak® Cone	50W PAR20
432NG-WH†*	Gold Alzak® Cone	
432NHZ-SC	Haze Alzak® Cone	
432NHZ-WH†*	Haze Alzak® Cone	
432NWHZ-ABZ	Wheat Haze Alzak® Cone	

432NWHZ-WH†* Wheat Haze Alzak® Cone

Angle-Cut Lensed Trim





nsea Irim		
431NB-WH [†] *	Black Alzak® Cone	45W PAR 16/
431NC-WH [†] *	Clear Alzak® Cone	50W PAR20
431NG-WH [†] *	Gold Alzak® Cone	
431NHZ-SC	Haze Alzak® Cone	
431NHZ-WH†*	Haze Alzak® Cone	
431NWHZ-ABZ	Wheat Haze Alzak® Cone	
431NWHZ-WH†*	Wheat Haze Alzak® Cone	

1/4" Pinhole with uniformity lens Downlight 1





willi dillidilliliy iciis	
Black Alzak® Reflector	45W PAR 16,
Black Alzak® Reflector	50W PAR20
Black Alzak® Reflector	
	Black Alzak® Reflector Black Alzak® Reflector

Adjustable 1 1/4" Pinhole with uniformity lens





4302N-WH**

Black Alzak® Reflector Black Alzak® Reflector Black Alzak® Reflector

45W PAR 16/ 50W PAR20

Downlight Regressed 1 3/4" Pinhole with uniformity lens





Black Alzak® Reflector

45W PAR 16/ 50W PAR20

Adjustable Regressed 1 3/4" Pinhole with uniformity lens





4301 N-WH**

Black Alzak® Reflector

45W PAR 16/ 50W PAR20

†Self Flanged: Replace "-WH" suffix with "-SF".

For self flanged reflector with optional white painted flange, replace "-SF" suffix with "-SFWH"

Flush Mount: *Replace "-WH" suffix with "-FM". **Add "-FM" to the Catalog #.

Flush Mount trims must be used with FMA4 Flush Mount Adapter, ordered separately.

ADJUSTABLE ACCENT (Trim Ring Catalog # Shown)

Angle-Cut Co

Cat. No.



Lamp Rating

ne		
438NB-ABZ	Black Alzak® Cone	60W PAR 16,
438NB-SC	Black Alzak® Cone	50W PAR20
438NB-WH [†] *	Black Alzak® Cone	
438NC-WH†*	Clear Alzak® Cone	
438NG-WH [†] *	Gold Alzak® Cone	
438NHZ-SC	Haze Alzak® Cone	
438NHZ-WH [†] *	Haze Alzak® Cone	
438NWHZ-ABZ	Wheat Haze Alzak® Cone	
438NWHZ-WH†*	Wheat Haze Alzak® Cone	

Description

20° Angle-Cut Cone



430NB-WH [†] *	Black Alzak® Cone
430NC-WH [†] *	Clear Alzak® Cone
430NG-WH [†] *	Gold Alzak® Cone
430NHZ-SC	Haze Alzak® Cone
430NHZ-WH [†] *	Haze Alzak® Cone
430NWHZ-ABZ	Wheat Haze Alzak® Cone
430NWHZ-WH†*	Wheat Haze Alzak® Cone

Slot Angle-Cut



ıt Cone		
436NB-ABZ	Black Alzak® Cone	60W PAR 16,
436NB-SC	Black Alzak® Cone	50W PAR20
436NB-WH [†] *	Black Alzak® Cone	
436NC-WH†*	Clear Alzak® Cone	
436NG-WH†*	Gold Alzak® Cone	
436NHZ-SC	Haze Alzak® Cone	
436NHZ-WH† *	Haze Alzak® Cone	
436NWHZ-ABZ	Wheat Haze Alzak® Cone	
436NWHZ-WH†*	Wheat Haze Alzak® Cone	

Angle-Cut Baffle



I35NB-ABZ	Black Baffle	60W PAR 16,
I35NB-SC	Black Baffle	50W PAR20
I35NB-WH	Black Baffle	
I35NW-WH	White Baffle	

Adjustable 1 1/4" Pinhole



1/4 Fillion		
433N-ABZ	Black Alzak® Reflector	60W PAR 16
433N-SC	Black Alzak® Reflector	50W PAR20
433N-WH**	Black Alzak® Reflector	

Adjustable 1 3/4" Pinhole



3/4" Pinnoie		
4335N-ABZ	Black Alzak® Reflector	60W PAR 16
4335N-SC	Black Alzak® Reflector	50W PAR20
4335N-WH**	Black Alzak® Reflector	

Slot Pinhole



4345N-WH** Black Alzak® Reflector 60W PAR 16/ 50W PAR20

Adjustable Regressed 1 3/4" Pinhole



4308N-WH** Black Alzak® Reflector 60W PAR 16/ 50W PAR20

WALL WASH (Trim Ring Catalog # Shown)

Lensed Wall Wash





439NB-WH[†]* Black Alzak® Cone 45W PAR 16/ 439NC-WH[†]* Clear Alzak® Cone 50W PAR20 Gold Alzak® Cone 439NG-WH[†]* 439NW-WH[†]* White Cone Haze Alzak® Cone 439NHZ-SC 439NHZ-WH†* Haze Alzak® Cone 439NWHZ-ABZ Wheat Haze Alzak® Cone 439NWHZ-WH†* Wheat Haze Alzak® Cone

Trim Ring Finish: ABZ - Classic Aged Bronze, BL - Black, SC - Satin Chrome, WH - White.